

## Ulna Nail

Specification		
Ulna or Radius	D	L
Ulna	Φ3	180
Ulna	Φ3	200
Ulna	Φ3	220
Ulna	Φ3	240
Ulna	Φ3.6	180
Ulna	Φ3.6	200
Ulna	Φ3.6	220
Ulna	Φ3.6	240

## Radius and Ulna Locking screws

Specification	
D	L
Φ3.5	10
Φ3.5	12
Φ3.5	14
Φ3.5	16
Φ3.5	18
Φ3.5	20
Φ3.5	22
Φ3.5	24
Φ3.5	26
Φ3.5	28
Φ3.5	30
Φ3.5	32
Φ3.5	34
Φ3.5	36
Φ3.5	38
Φ3.5	40

## Radius Nail

Specification			
Ulna or Radius	Left or right	D	L
Radius	Left	Φ3	160
Radius	Left	Φ3	180
Radius	Left	Φ3	200
Radius	Left	Φ3.6	160
Radius	Left	Φ3.6	180
Radius	Left	Φ3.6	200
Radius	Right	Φ3	160
Radius	Right	Φ3	180
Radius	Right	Φ3	200
Radius	Right	Φ3.6	160
Radius	Right	Φ3.6	180
Radius	Right	Φ3.6	200

## Radius and Ulna End Caps

## Radius and Ulna nail

### Features:

1. Anatomical nail design;
2. Proximal locking design achieves rotational stability.
3. Recess and flexible shaft design enables small incision without expanding the cavity.
4. Minimally invasive surgery without much scars.
5. Our products are manufactured using one or more of the following materials: commercially pure titanium(ISO 5832-2, ASTM F67),Ti6Al4V alloy(ISO 5832-3, ASTM F1472).



### Indications:

1. Forearm fracture;
2. Comminuted forearm shaft fracture;
3. Segmental forearm fracture;

